

F0459 | API GRAVITY DROP ADAPTOR

The F0459 range of API Gravity Drop Adaptors has been specifically designed for use with API adaptors when discharging product and will couple to any adaptor made in accordance with API RP1004.

APPROVALS

- * Conforms to API RP1004
- * Emco Wheaton Surelok™ conforming to MIL-C-27487 specification

FEATURES AND BENEFITS

- * High quality, lightweight die cast body.
- * Brass cams reduce wear on API nose and eliminate corrosion.
- * Internal shoulder to grip adaptor nose and support weight of product hose.
- * Stainless steel chain supplied as standard for attachment to API adaptor.
- * Buna seal fitted as standard.
- * 2½", 3" and 4" Surelok™ outlet variants available.
- * 3" and 4" threaded outlet variants available.
- * Suitable for all API Adaptors which conform to RP1004.
- * Size / Weight

* 4" API x 3" C&G	1.81 kg
* 4" API x 4" C&G	2.27 kg
* 4" API x 2½" C&G	1.40 kg
* 4" API x 3" BSPP Male	1.81 kg
* 4" API x 4" BSPP Male	2.27 kg
* 4" API x 3" BSPP Female	1.81 kg



WHEN SPECIFYING API GRAVITY DROP ADAPTORS FOR YOUR VEHICLE, THE FOLLOWING POINTS SHOULD BE CONSIDERED:

- * Outlet connection size required.
- * Threaded or Surelok™ connection.
- * Quantity required per vehicle.

F0459

Better by Design



EMCO WHEATON

A Gardner Denver Product

EMCO WHEATON UK Limited
 Channel Road · Westwood Industrial Estate
 Margate, Kent CT9 4JR · UK
 Phone + 44 1843 221521 · Fax +44 1843 295444
www.emcowheaton.com · assist@emcowheaton.com

Sheet Ref. CSF0459 - May 2006 - Revision 0

As a part of a continuous commitment to product development the company reserves the right to alter the specification of its products without prior notice